

# ELECTRIC CAR SPECIFICATIONS



## DIMENSIONS

OVERALL LENGTH	94.3 in (2395 mm)
OVERALL WIDTH	47.2 in (1200 mm)
OVERALL HEIGHT (Suntop)	70.4 in (1789 mm)
OVERALL HEIGHT (No Suntop)	46.9 in (1190)
WHEELBASE	64.6 in (1640 mm)
FRONT WHEEL TREAD	34.3 in (870 mm)
REAR WHEEL TREAD	38.6 in (980 mm)
MINIMUM GROUND CLEARANCE	4.3 in (110 mm)

## POWER SUPPLY / DRIVE TRAIN

MOTOR	Hitachi 48-volt high-efficiency, shunt wound motor with internal solid state tachometer
OUTPUT RATING	3.5 hp (2.6 kW) for 30 minutes
MOTOR CONTROL UNIT	Yamaha-built solid state microprocessor with high-efficiency MOSFET switching. 270 amp armature output, 20 amp field output
TRANSAXLE	EnduraDrive™ direct coupled transaxle equipped with high-precision helical gears, 12.49:1 drive axle ratio
BATTERIES	Four 12-volt Trojan T1275 Batteries
CHARGER	Yamaha-built automatic microprocessor-based high frequency switching- regulated charger with I.E.I.-type charging profile, an industry first. 17 amp DC max output at 48 volts, 9.5 amp 120 volt AC. Underwriters Laboratories (U.L.) Listed. C.S.A. Certified

## CHASSIS

FRAME	HybriCore™ Chassis features a robotically welded automotive ladder-style frame mated to a polypropylene structural floor. Frame components are protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatically applied polyester/urethane powder topcoat
BODY	Custom-formulated thermoplastic olefin, painted with a two-part top coat of high-luster automotive-grade polyurethane
STEERING	Self-compensating double reduction helical rack-and-pinion, permanently lubricated with sealed, greaseless tie-rod ends
FRONT SUSPENSION	Tru-Trak II™ fully independent automotive-style strut suspension
REAR SUSPENSION	Unit swing arm with coil springs over hydraulic shock absorbers
BRAKES	Maintenance-free internal transaxle disc brake
SEATING	Seamless, fabric-backed vinyl bonded to pure, virgin foam contoured seat cushions and mated to a warp- and moisture-resistant polypropylene bottom, strengthened with plated steel inserts.
BUMPERS	Front and rear 5 mph energy-absorbing bumpers

## PERFORMANCE

MAX FORWARD SPEED	15 mph (24 km/h)
MAX REVERSE SPEED	5 mph (8.1 km/h)
TURNING RADIUS	9.2 ft (2.8 m)

## GENERAL

DRY WEIGHT (less batteries)	536 lbs (243 kg)
TIRE SIZE	18.00 x 8.50-8.00 (4-ply rating)
SEATING CAPACITY	2 persons
AVAILABLE PAINT COLORS	Glacier, Emerald, Garnet, Sandstone Metallic, Cobalt Metallic, Anthracite Metallic, Onyx Metallic
AVAILABLE SEAT & SUNTOP COLORS	Stone

## WARRANTY

WARRANTY	Standard 3-year limited vehicle warranty.
----------	---