

# THE MAXGUARD® DIFFERENCE

## Trojan's Proprietary Maxguard® Separator



## Versus competitors' Wide Ribbed Separator



Only genuine Trojan deep cycle batteries feature the Maxguard® Advanced Design Separator. Benefits include extended life, sustained performance, less water consumption and lower maintenance costs.

## Wide Ribbed Separators Fail in Service



## TROJAN'S COMPLETE GOLF LINE-UP

BCI Group Size	Type	Capacity <sup>A</sup> (Minutes)		5 Hr <sup>B</sup> Rate (AH)	20 Hr <sup>C</sup> Rate (AH)	Terminal Config.	Dimensions <sup>D</sup> inches (mm)			Weight lbs (kg)
		@25 Amps	@75 Amps				L	W	H	
<b>DEEP CYCLE - 6 VOLT</b>										
GC2	T-605	383	105	175	210	2,6,11	10 3/8 (264)	7 1/8 (181)	10 7/8 (276)	58 (26)
GC2	T-105	447	115	185	225	1,2,6,11	10 3/8 (264)	7 1/8 (181)	10 7/8 (276)	62 (28)
GC2	T-125	488	132	195	240	2,6,11	10 3/8 (264)	7 1/8 (181)	10 7/8 (276)	66 (30)
GC2H	T-145	530	145	215	260	2,6,11	10 3/8 (264)	7 1/8 (181)	11 5/8 (295)	72 (33)
DIN	TE35	500	135	200	245	2	9 5/8 (244)	7 1/2 (191)	10 7/8 (276)	68 (31)
<b>DEEP CYCLE - 8 VOLT</b>										
GC8	T-860	-	E	125	150	6	10 3/8 (264)	7 1/8 (181)	10 7/8 (276)	56 (25)
GC8	T-875	295	F	145	170	2,6,11	10 3/8 (264)	7 1/8 (181)	10 7/8 (276)	63 (29)
GC8	T-890	340	G	155	190	2,6,11	10 3/8 (264)	7 1/8 (181)	10 7/8 (276)	69 (31)
<b>DEEP CYCLE - 12 VOLT</b>										
NA	T1275	280	H	120	150	13	12 7/8 (327)	7 (178)	10 7/8 (276)	82 (37)

- A. Reserve Capacity or Capacity - The number of minutes a battery can be discharged at 25 or 75 amps (56 amps for 8 volt batteries) at 27°C (80°F) and maintain a voltage above 1.75 v/cell.
- B. 5 hour rate is based on IEC (International Electrotechnical Commission) temperature standard of 30°C (86°F).
- C. 20 hour rate is a BCI sanctioned rating expressing ampere hours required to achieve an end voltage of 1.75 v/cell at 27°C (80°F) and represents the battery's maximum capacity.
- D. All dimensions taken from bottom of battery to top of terminal. Heights may vary according to type of terminals specified.
- E. Capacity @56 Amps is 90 Minutes.
- F. Capacity @56 Amps is 117 Minutes.
- G. Capacity @56 Amps is 132 Minutes.
- H. Capacity @56 Amps is 102 Minutes.

## TERMINAL CONFIGURATIONS



1- "L" Terminal (LT)



6 - Low Profile Terminal (LPT)



2 - Automotive Post (AP)



11- Universal Terminal (UT)



13- Embedded Low Profile Terminal (ELPT)



T-605



T-105



T-125



T-875



T-1275



For a Master Distributor near you, call 800-423-6569 or 562-946-8381 or visit [www.trojanbattery.com](http://www.trojanbattery.com).  
Clean energy for life™